



نوع پمپ	نوع الکتروموتور 3~	جریان (آمپر)	توان P2			قطر لوله قطر چاه (اینچ)		میزان آبدهی Q	n = 2900 rpm, 50 Hz (دور در دقیقه)											DM	L	L1	W	W
			A	KW	HP	in	in		110	140	150	160	170	180	200	220	240	260	حداکثر قطر مجموعه					
RP 425	B - RP 425 NB - RP 425	400 V(380-415)				φ	φ	m <sup>3</sup> /h	30.6	38.9	41.7	44.5	47.2	50	55.6	61.1	66.7	72.2	mm	mm	mm	kg	kg	
RP 425/1	NB-RP-425/1	7A 223/2	47	22	30	10	6	ارتفاع آبدهی H m	36	34	33	32	31	30	28	25	22	19	220	1895	745	180	50	
RP 425/2aa	NB-RP-425/2aa	9I 303/2	63	30	41	10	6		52	48	47	45	43	41	36	31	26	--	220	2245	905	247	70	
RP 425/2a	NB-RP-425/2a	9I 383/2	79	38	52	10	6		62	58	57	55	53	51	46	41	36	--	220	2245	905	248	71	
RP 425/2	NB-RP-425/2	9I 453/2	93	45.5	62	10	6		68	65	64	63	61	60	56	51	46	41	220	2335	905	282	72	
RP 425/3aa	NB-RP-425/3aa	9I 523/2	107	52	70	10	8		89	85	83	81	79	77	71	64	56	--	220	2605	1065	320	106	
RP 425/3a	NB-RP-425/3a	9I 603/2	122	60	80	10	8		98	94	92	90	88	85	79	72	64	55	220	2735	1065	346	107	
RP 425/3	NB-RP-425/3	9I 673/2	137	67	90	10	8		104	100	98	96	94	92	86	79	71	63	220	2735	1065	347	108	
RP 425/4aa	NB-RP-425/4aa	9I 733/2	154	73.5	100	10	8		120	115	113	110	108	105	97	88	80	70	220	2985	1225	379	122	
RP 425/4a	NB-RP-425/4a	9I 833/2	166	83	110	10	8		127	122	120	118	115	112	105	95	86	76	220	3165	1225	413	122	
RP 425/4	NB-RP-425/4	9I 923/2	188	92	125	10	8		135	130	128	126	123	120	112	103	92	82	220	3165	1225	414	123	
RP 425/5	NB-RP-425/5	12I 1103/2	235	110	150	12	8	170	165	162	159	156	152	141	129	115	101	235	3207	1500	460	140		
RP 425/6a	NB-RP-425/6a	12I 1303/2	266	130	175	12	8	191	185	183	180	176	171	159	144	129	112	235	3367	1660	535	168		
RP 425/6	NB-RP-425/6	12I 1503/2	307	150	200	12	8	205	200	197	194	190	185	173	159	142	123	235	3597	1660	587	169		
RP 425/7a	NB-RP-425/7a	12I 1503/2	307	150	200	12	8	214	209	206	203	198	193	181	167	150	130	235	3757	1820	600	182		
RP 425/7	NB-RP-425/7	12I 1853/2	390	185	250	12	8	236	232	231	228	224	219	207	191	170	146	235	3907	1820	639	185		
RP 425/7	NB-RP-425/7	12 A 1853/2	380	185	250	14	8	236	232	231	228	224	219	207	191	170	146	280	4130	1820	918	185		
RP 425/8	NB-RP-425/8	12I 1853/2	390	185	250	12	8	267	265	262	258	253	247	231	211	187	162	235	4067	1980	655	201		
RP 425/8	NB-RP-425/8	12 A 1853/2	380	185	250	14	8	267	265	262	258	253	247	231	211	187	162	280	4290	1980	934	201		
RP 425/9	NB-RP-425/9	12 A 2203/2	460	220	300	14	8	300	296	293	288	283	275	256	231	206	180	280	4612	2140	990	217		
RP 425/10	NB-RP-425/10	12 A 2203/2	460	220	300	14	8	332	326	323	317	311	302	279	253	225	198	280	4772	2300	1006	233		

η% راندمان	65	71.5	73.5	75	76	77	77.5	76	73.5	71
NPSH (m)*	8	9	9.3	9.5	9.8	10	10.3	10.6	10.9	11